## What Is Claimed Is:

1\ A closure comprising:

a tok wall;

10

IU

1

15

a skirt surrounding said top wall and extending downwardly therefrom with a terminating edge opposite said top wall defining an open bottom and;

a bead integral with an inner surface of said skirt and spaced from said top wall; and,

a helical thread having a substantially flat upper thread surface circumscribing said inner surface of said skirt, said thread having a lower thread profile end of a first depth and an upper thread profile end of a second depth, said first depth being greater than said second depth, said upper thread profile extending downwardly from said non-back-off bead.

- 2. The closure of Claim 1, including a seal on the inner surface of said top wall.
- 3. The closure of Claim 2, said seal being positioned between said top wall and said bead.

- 5. The closure of Claim 2, said seal being linerless.
- 6. The closure of Claim 1, said thread being tapered to a second depth terminating coincident to said inner surface of said skirt prior to reaching said bead.
- 7. The closure of Claim 6, said second depth further tapering flush with said inner surface of said skirt.

ф

Ш

# E. E.

15

- 8. The closure of Claim 7, said second depth ending at a point coincident with a bead disposed between said top wall and said second depth.
- 9. The closure of Claim 1, wherein said first depth is about .0475 inches and said second depth is about .01 inches.
- 10. The closure of Claim 9, said thread being further tapered to a nominal depth terminating prior to reaching said bead.
- 11. The closure of Claim 10, said thread diminishing in depth between said first and second depths.

15

- 12. The closure of Claim 9, said thread diminishing in depth over an arc of between 45° and 120° from said upper thread profile end.
- 13. The closure of Claim 9, said thread diminishing in 5 depth over a 90 arc from said upper thread profile end.
  - 14. A closure comprising:
  - a top wall and kirt depending from said top wall;
  - a bead integral with an inner surface of said skirt and spaced from said top wall; and,
  - a helical thread having a lower thread portion of a first depth and an upper thread portion of a second depth, said first depth being greater than said second depth, said upper thread portion of said thread extending downwardly from said bead.
  - 15. The closure of Claim 14, said thread being tapered to a depth terminating coincident to said inner surface of said skirt prior to reaching said bead.
    - 16. The closure of Claim 14, said thread being variable in depth over an arc of about 90° of said upper thread portion end.

- 17. The closure of Claim 14, wherein a seal is located between said bead and said top wall.
  - 18. \A closure comprising:

to

177

Ū

.... H (III

÷

15

- a top wall and an annular skirt depending from said top 5 wall;
  - a bead integral with an inner surface of said skirt and spaced from said top wall;
  - a helical thread having a lower thread profile end of a first depth and an upper thread profile end of a second depth, said first depth being greater than said second depth, said upper profile extending downwardly from said bead and said thread having a flat upper surface.

said thread being tapered to a depth terminating coincident to said inner surface of said skirt prior to reaching said bead; and,

said thread being variable in depth over an arc of between 45° and 120° from said upper thread profile end.

- 19. The closure of Claim 19, wherein a seal is located between said bead and said top wall.
  - 20. A closure, comprising:

10

CE 63 EP

ļ±

- a top wall and annular skirt depending therefrom;
- a helically circumscribing thread integral with an inner surface of said skirt;

said thread having a substantially flat upper thread surface;

said thread takering into said skirt beneath said bead over an arc of between 45° to about 120°; and,

said thread being tapered to a depth flush with said inner surface of said skirt prior to reaching said top wall.

- 21. A closure, comprising:
  - a circular top wall and skirt depending therefrom;
- a helical thread circumscribing an inner surface of said skirt and having a flat upper surface along its entire

Closure Having an Improved Thread Design Inventor: William D. Sprick Atty Docket #: CG-614

length, said flat upper surface being at an angle of about 90° to said skirt;

said helical thread having a lower profile of a first depth of about .0475 inches and an upper profile of a second depth of about .01 inch;

said first depth being greater than said second depth such that said upper profile tapers into said skirt sidewall from said second depth to a third depth of about 0 (zero) inches.